

APPLICATION FOR UNITED STATES PATENT

in the name of

**Alfred A. Barney, Mouni G. Bawendi,
Daniel G. Nocera, Christina M. Rudzinski,
Vikram C. Sundar, and Glen W. Walker**

for

TEMPERATURE-SENSING COMPOSITION

Fish & Richardson P.C.
601 Thirteenth Street, NW
Washington, DC 20005
Tel.: (202) 783-5070
Fax: (202) 783-2331

ATTORNEY DOCKET:

01997-286001

TEMPERATURE-SENSING COMPOSITION

FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with government support under Contract No. DMR-98-08941 from the National Science Foundation and Subcontract No. 3012S1 from Contract No. F33615-98-C-3012 from Air Force Office of Sponsored Research. The government may
5 have certain rights in the invention.

TECHNICAL FIELD

This invention relates to a temperature-sensing composition.

BACKGROUND

Specialty compositions, which can contain luminescent probes that are sensitive to
10 environmental parameters such as, for example, temperature and pressure, have a variety of analytical applications. For example, specialty compositions can form coatings used to remotely determine the surface temperature of an object in a non-invasive manner.

Objects can be coated with films containing the sensing compositions which emit
15 light of varying intensities, depending on temperature and oxygen pressure. In a specific example, temperature-sensing compositions can be used in combination with compositions for measuring the pressure of an oxygen-containing gas on an aerodynamic surface by oxygen-quenching of luminescent pressure sensing compositions. These compositions can be used to provide convenient and inexpensive methods for determining pressure or temperature
20 maps at surfaces. An example of a pressure-sensing composition includes a phosphorescent porphyrin which has an emission that is quenched by oxygen. This quenching can be used to quantitatively measure the static pressure on the surface of the object. In certain circumstances, the emission of the pressure-sensing composition can have temperature dependence in addition to pressure dependence. Accordingly, pressure measurements containing a temperature-sensing composition can be corrected by sensing fluctuations in the
25 temperature in addition to pressure.

SUMMARY

Temperature-sensing compositions can include an inorganic material, such as a semiconductor nanocrystal. The nanocrystal can be a dependable and accurate indicator of temperature. The intensity of emission of the nanocrystal varies with temperature and can be highly sensitive to surface temperature. The nanocrystals can be processed with a binder to form a matrix, which can be varied by altering the chemical nature of the surface of the nanocrystal. A nanocrystal with a compatibilizing outer layer can be incorporated into a coating formulation and retain its temperature sensitive emissive properties.

In one aspect, a method of sensing temperature includes providing a temperature sensor including a matrix on a surface of a substrate, the matrix comprising a semiconductor nanocrystal in a binder, irradiating a portion of the sensor with an excitation wavelength of light, detecting emission of light from the sensor, and determining the temperature from the emission of light from the sensor.

In another aspect, a temperature sensor includes a matrix containing a semiconductor nanocrystal. The matrix can be formed from a semiconductor nanocrystal and a binder.

In another aspect, a temperature-sensing coating includes a matrix on a surface of a substrate. The matrix can include a semiconductor nanocrystal in a binder.

In another aspect, a temperature-sensing paint includes a semiconductor nanocrystal in a binder and a deposition solvent. The semiconductor nanocrystal can emit light independent of oxygen pressure and dependent upon temperature upon irradiation by an excitation wavelength of light. The emission intensity can change by 1.1-1.6% per degree centigrade. The paint can include a pressure-sensitive composition, the pressure-sensitive composition emitting light dependent upon oxygen pressure upon irradiation by an excitation wavelength of light. The pressure-sensitive composition can include a porphyrin, such as a platinum porphyrin. The deposition solvent can include an alcohol.

In another aspect, a method of manufacturing a temperature-sensing paint includes combining a semiconductor nanocrystal, a binder, and a deposition solvent to form a paint. The paint can be used to manufacture a temperature sensor by depositing a temperature-sensing paint on a surface of a substrate.

The semiconductor nanocrystal can include a group II-VI semiconductor, a group III-V semiconductor, or group IV semiconductor, for example, ZnS, ZnSe, ZnTe, CdS, CdSe;

CdTe, HgS, HgSe, HgTe, AlN, AlP, AlAs, AlSb, GaN, GaP, GaAs, GaSb, InN, InP, InAs, InSb, TiN, TiP, TiAs, TiSb, PbS, PbSe, PbTe, or mixtures thereof. The semiconductor nanocrystal can be overcoated with a second semiconductor material. The semiconductor nanocrystal can include an organic or organometallic overlayer, the overlayer making the nanocrystal dispersible in the binder. The overlayer can include a hydrolyzable moiety, such as a metal alkoxide.

The nanocrystal can be a member of a substantially monodisperse core population, such as a population exhibiting less than a 15% rms deviation in diameter of the nanocrystal, which can emit light in a spectral range of no greater than about 75 nm full width at half max (FWHM). The nanocrystal can photoluminesce with a quantum efficiency of at least 10% and can have a particle size in the range of about 15 Å to about 125 Å.

The binder can include an organic polymer or inorganic matrix.

The details of one or more embodiments are set forth in the accompanying drawings and the description below. Other features and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

Figure 1 is a graph depicting emission spectra of ZnS-capped CdSe nanocrystals in a poly(lauryl methacrylate) matrix irradiated at 480 nm at various temperatures.

Figure 2 is a graph depicting integrated emission intensity of the ZnS-capped CdSe nanocrystals dispersed in a matrix over a range of temperatures.

DETAILED DESCRIPTION

A temperature-sensing composition can include a semiconductor nanocrystal. Nanocrystals composed of semiconductor material can be illuminated with a light source at an absorption wavelength to cause an emission at an emission wavelength, the emission having a frequency that corresponds to the band gap of the quantum confined semiconductor material. The band gap is a function of the size of the nanocrystal. Nanocrystals having small diameters can have properties intermediate between molecular and bulk forms of matter. For example, nanocrystals based on semiconductor materials having small diameters can exhibit quantum confinement of both the electron and hole in all three dimensions, which leads to an increase in the effective band gap of the material with decreasing crystallite size.

Consequently, both the optical absorption and emission of nanocrystals shift to the blue (i.e., to higher energies) as the size of the crystallites decreases.

The emission from the nanocrystal can be a narrow Gaussian emission band that can be tuned through the complete wavelength range of the ultraviolet, visible, or infrared regions of the spectrum by varying the size of the nanocrystal, the composition of the nanocrystal, or both. For example, CdSe can be tuned in the visible region and InAs can be tuned in the infrared region. The narrow size distribution of a population of nanocrystals can result in emission of light in a narrow spectral range. The population can exhibit less than a 15% rms deviation in diameter of the nanocrystals, preferably less than 10%, more preferably less than 5%. Spectral emissions in a narrow range of no greater than about 75 nm, preferably 60 nm, more preferably 40 nm, and most preferably 30 nm full width at half max (FWHM) can be observed. The breadth of the emission decreases as the dispersity of nanocrystal diameters decreases. Semiconductor nanocrystals can have high emission quantum efficiencies such as greater than 10%, 20%, 30%, 40%, 50%, 60%, 70%, or 80%.

The narrow emission band of the nanocrystal can improve the performance and reliability of the temperature-sensing composition relative to compositions that include conventional molecular probes that have broad, fixed wavelength emission bands. In addition, the excitation profile of the nanocrystal can be broad and intense, which can allow efficient excitation of the nanocrystals across a range of wavelengths in the visible spectrum. These factors together offer flexibility in the design of optical detection systems for temperature-sensing applications.

The nanocrystal can be chemically stable when illuminated. The nanocrystal can be relatively unreactive with other materials, which can permit it to be used as a temperature probe in a wide variety of environments. For example, the emission of the nanocrystal can be independent of gas pressure, such as oxygen pressure, or resistant to degradation in the presence of oxygen. Conventional organic temperature probes can degrade rapidly when illuminated, decreasing the useful lifespan of the coatings that contain them. A variety of applications can be envisioned for temperature-sensing compositions that contain nanocrystals on the well-defined temperature dependent emission properties of the nanocrystal. For example, in aerospace engineering, nanocrystal-based temperature

indicators can be used as the active component in temperature sensitive paints or as an internal temperature calibrant for two-component pressure sensitive paints.

Methods of preparing monodisperse semiconductor nanocrystals include pyrolysis of organometallic reagents, such as dimethyl cadmium, injected into a hot, coordinating solvent.

5 This permits discrete nucleation and results in the controlled growth of macroscopic quantities of nanocrystals. Preparation and manipulation of nanocrystals are described, for example, in U.S. Appln. No. 08/969,302, incorporated herein by reference in its entirety. The method of manufacturing a nanocrystal is a colloidal growth process. Colloidal growth occurs by rapidly injecting an M donor and an X donor into a hot coordinating solvent. The
10 injection produces a nucleus that can be grown in a controlled manner to form a nanocrystal. The reaction mixture can be gently heated to grow and anneal the nanocrystal. Both the average size and the size distribution of the nanocrystals in a sample are dependent on the growth temperature. The growth temperature necessary to maintain steady growth increases with increasing average crystal size. The nanocrystal is a member of a population of
15 nanocrystals. As a result of the discrete nucleation and controlled growth, the population of nanocrystals obtained has a narrow, monodisperse distribution of diameters. The monodisperse distribution of diameters can also be referred to as a size. The process of controlled growth and annealing of the nanocrystals in the coordinating solvent that follows nucleation can also result in uniform surface derivatization and regular core structures. As
20 the size distribution sharpens, the temperature can be raised to maintain steady growth. By adding more M donor or X donor, the growth period can be shortened.

The M donor can be an inorganic compound, an organometallic compound, or elemental metal. M is cadmium, zinc, magnesium, mercury, aluminum, gallium, indium or thallium. The X donor is a compound capable of reacting with the M donor to form a
25 material with the general formula MX. Typically, the X donor is a chalcogenide donor or a pnictide donor, such as a phosphine chalcogenide, a bis(silyl) chalcogenide, dioxygen, an ammonium salt, or a tris(silyl) pnictide. Suitable X donors include dioxygen, bis(trimethylsilyl) selenide ((TMS)₂Se), trialkyl phosphine selenides such as (tri-n-octylphosphine) selenide (TOPSe) or (tri-n-butylphosphine) selenide (TBPSe), trialkyl
30 phosphine tellurides such as (tri-n-octylphosphine) telluride (TOPTe) or hexapropylphosphorustriamide telluride (HPPTTe), bis(trimethylsilyl)telluride ((TMS)₂Te),

bis(trimethylsilyl)sulfide ((TMS)₂S), a trialkyl phosphine sulfide such as (tri-n-octylphosphine) sulfide (TOPS), an ammonium salt such as an ammonium halide (e.g., NH₄Cl), tris(trimethylsilyl) phosphide ((TMS)₃P), tris(trimethylsilyl) arsenide ((TMS)₃As), or tris(trimethylsilyl) antimonide ((TMS)₃Sb). In certain embodiments, the M donor and the X donor can be moieties within the same molecule.

A coordinating solvent can help control the growth of the nanocrystal. The coordinating solvent is a compound having a donor lone pair that, for example, has a lone electron pair available to coordinate to a surface of the growing nanocrystal. Solvent coordination can stabilize the growing nanocrystal. Typical coordinating solvents include alkyl phosphines, alkyl phosphine oxides, alkyl phosphonic acids, or alkyl phosphinic acids, however, other coordinating solvents, such as pyridines, furans, and amines may also be suitable for the nanocrystal production. Examples of suitable coordinating solvents include tri-n-octyl phosphine (TOP) and tri-n-octyl phosphine oxide (TOPO). Technical grade TOPO can be used.

Size distribution during the growth stage of the reaction can be estimated by monitoring the absorption line widths of the particles. Modification of the reaction temperature in response to changes in the absorption spectrum of the particles allows the maintenance of a sharp particle size distribution during growth. Reactants can be added to the nucleation solution during crystal growth to grow larger crystals. By stopping growth at a particular nanocrystal average diameter and choosing the proper composition of the semiconducting material, the emission spectra of the nanocrystals can be tuned continuously over the wavelength range of 400 nm to 800 nm. The nanocrystal has a diameter of less than 150 Å. A population of nanocrystals has average diameters in the range of 15 Å to 125 Å.

The nanocrystal can be a member of a population of nanocrystals having a narrow size distribution. The nanocrystal can be a sphere, rod, disk, or other shape. The nanocrystal can include a core of a semiconductor material. The nanocrystal can include a core having the formula MX, where M is cadmium, zinc, magnesium, mercury, aluminum, gallium, indium, thallium, or mixtures thereof, and X is oxygen, sulfur, selenium, tellurium, nitrogen, phosphorus, arsenic, antimony, or mixtures thereof.

The core can have an overcoating on a surface of the core. The overcoating can be a semiconductor material having a composition different from the composition of the core.

The overcoat of a semiconductor material on a surface of the nanocrystal can include a group II-VI, III-V or IV semiconductor, such as, for example, ZnO, ZnS, ZnSe, ZnTe, CdO, CdS, CdSe, CdTe, MgO, MgS, MgSe, MgTe, HgO, HgS, HgSe, HgTe, AlN, AlP, AlAs, AlSb, GaN, GaP, GaAs, GaSb, InN, InP, InAs, InSb, TiN, TiP, TiAs, TiSb, TeSb, PbS, PbSe, PbTe, or mixtures thereof. For example, ZnS, ZnSe or CdS overcoatings can be grown on CdSe or CdTe nanocrystals. An overcoating process is described, for example, in U.S. Application No. 08/969,302, incorporated herein by reference in its entirety. By adjusting the temperature of the reaction mixture during overcoating and monitoring the absorption spectrum of the core, over coated materials having high emission quantum efficiencies and narrow size distributions can be obtained.

The particle size distribution can be further refined by size selective precipitation with a poor solvent for the nanocrystals, such as methanol/butanol as described in U.S. Application No. 08/969,302, incorporated herein by reference. For example, nanocrystals can be dispersed in a solution of 10% butanol in hexane. Methanol can be added dropwise to this stirring solution until opalescence persists. Separation of supernatant and flocculate by centrifugation produces a precipitate enriched with the largest crystallites in the sample. This procedure can be repeated until no further sharpening of the optical absorption spectrum is noted. Size-selective precipitation can be carried out in a variety of solvent/nonsolvent pairs, including pyridine/hexane and chloroform/methanol. The size-selected nanocrystal population can have no more than a 15% RMS deviation from mean diameter, preferably 10% RMS deviation or less, and more preferably 5% RMS deviation or less.

Transmission electron microscopy (TEM) can provide information about the size, shape, and distribution of the nanocrystal population. Powder x-ray diffraction (XRD) patterns can provided the most complete information regarding the type and quality of the crystal structure of the nanocrystals. Estimates of size are also possible since particle diameter is inversely related, via the X-ray coherence length, to the peak width. For example, the diameter of the nanocrystal can be measured directly by transmission electron microscopy or estimated from x-ray diffraction data using, for example, the Scherrer equation. It also can be estimated from the UV/Vis absorption spectrum.

The outer surface of the nanocrystal can include layer of compounds derived from the coordinating solvent used during the growth process. The surface can be modified by

repeated exposure to an excess of a competing coordinating group to form an overlayer. For example, a dispersion of the capped nanocrystal can be treated with a coordinating organic compound, such as pyridine, to produce crystallites which disperse readily in pyridine, methanol, and aromatics but no longer disperse in aliphatic solvents. Such a surface exchange process can be carried out with any compound capable of coordinating to or bonding with the outer surface of the nanocrystal, including, for example, phosphines, thiols, amines and phosphates. The nanocrystal can be exposed to short chain polymers which exhibit an affinity for the surface and which terminate in a moiety having an affinity for a suspension or dispersion medium. Such affinity improves the stability of the suspension and discourages flocculation of the nanocrystal.

The compound forming the overlayer can have a reactive group that can react with another compound to bond the nanocrystal to the binder. The binder can form a matrix. The matrix can be an organic polymer matrix, such as a polyacrylate matrix, or an inorganic matrix, such as a sol-gel-derived matrix.

The reactive group can be a polymerizable moiety, such as an acrylate moiety, a styryl moiety, or a hydrolyzable moiety, for example, silicon alkoxide, titanium alkoxide, zirconium alkoxide, or other metal alkoxide, metal amide, metal carboxylate, or metal halide groups. The reactive groups can react with each other, or with reactive groups of other compounds or monomers, to form a solid matrix containing the nanocrystals. In this manner, the nanocrystal can be incorporated into a solid matrix formed in part by reaction of the reactive groups. Alternatively, the reactive group can be a functionality, such as an amino or hydroxyl group, that can react with a multifunctional component, such as a dicarboxylic acid, or reactive derivative thereof, or a diisocyanate, to form a solid matrix containing the nanocrystals.

The temperature-sensing composition can be applied to a substrate as a paint. The paint can include a binder and a deposition solvent. The binder can produce a film on a surface of an object upon evaporation of solvent. The binder can include an organic or inorganic polymer or prepolymer, for example, a polymer or prepolymer typically used in a paint composition. The binder can form a film by chemical reaction with atmospheric moisture, a heat or light induced reaction, a chemical interaction with other components within the paint, such as the nanocrystal overlayer, or combinations thereof. The binder can

include a silicone polymer, for example, a thermoplastic silicone copolymer or dimethyl polysiloxane, a silicone co-polymers such as silicone-polyurethane or silicone-polyester copolymers, an acrylate or urethane polymer or prepolymer, or a hydrolyzable composition including a silicon alkoxide, a titanium alkoxide, a zirconium alkoxide, an aluminum
5 alkoxide, or other metal alkoxide that can form an inorganic matrix. The deposition solvent is a solvent that dissolves the nanocrystal and binder and can be sufficiently volatile to produce a smooth film. The deposition solvent can include 1,1,1-trichloroethane, dichloromethane, ethyl alcohol, butyl alcohol, isopropyl alcohol, cyclohexane, or mixtures thereof.

10 The paint can be applied to a substrate to form a film. A white substrate can improve the performance of the sensor by reflecting the emitted light more completely. The film can be thin, for example, 1-100, 2-50, 3-20, or 5-10 microns in thickness. Film thickness can be determined using an ultraviolet/visible spectrometer by measuring the optical absorption of the nanocrystal and applying Beer's law. The nanocrystal can be uniformly distributed in the
15 film. The coated surface can be irradiated with the excitation wavelength. While the coated object is irradiated, the emission wavelength can be monitored, for example, with a photomultiplier tube. The intensity of the emission can be compared with predetermined calibration values to produce measurements of the temperature on the surface. By distributing nanocrystals over a surface and monitoring emission at particular regions on the
20 surface, a quantitative map of temperature on the surface can be obtained.

The temperature-sensing composition can be used in the preparation of pressure sensitive paints, such as those described in Gouterman *et al.*, U.S. Patent No. 5,186,046, incorporated by reference in its entirety. The pressure sensitive paint includes a pressure-sensing composition that produces an emission that is dependent on pressure. Any
25 temperature dependence can be corrected by including the temperature-sensing composition in the pressure sensitive paint. A pressure-sensing composition can include a porphyrin, such as a platinum porphyrin, in particular, platinum octaethylporphyrin. For porphyrins, the individual molecules should be separated by at least about 50Å to prevent triplet-triplet deactivation. This intermolecular separation corresponds to a porphyrin concentration of
30 about 10^{-2} molar. The excitation spectrum for platinum octaethylporphyrin displays a strong excitation band in the near ultraviolet region of the visible spectrum at approximately 380 nm

and a weaker band in the green region at approximately 540 nm and an emission in the red region of the visible spectrum at approximately 650 nm. Platinum octaethylporphyrin has an emission quantum yield of approximately 90%.

In a pressure sensitive paint, either the excitation wavelength or the emission wavelength of the pressure-sensing composition and the temperature-sensing composition are different. When a common excitation wavelength is present, the emission wavelength maxima can be separated by 10 nm or more, or 20 nm or more, so that the data for each composition can be measured separately. One advantage of a temperature-sensing composition including a nanocrystal is that the emission wavelength of the nanocrystal can be selected so that the emission does not interfere with the emission from the pressure-sensing composition. The excitation wavelength can be selected so that the nanocrystal and the pressure-sensing composition are excited at the same wavelength.

When different emission wavelengths are generated, the intensities can be measured by rotating different interference filters in front of a detection device, such as a video camera, or a photomultiplier tube, during irradiation with the excitation wavelength. Alternatively, a diode array detector can be used to monitor emissions.

EXAMPLES

Semiconductor nanocrystals were shown to be emissive temperature probes in solution and in polymer matrices

Highly emissive nanocrystals of cadmium selenide (CdSe) were synthesized by colloidal growth, such as, for example, the method described in U.S. Appln. No. 08/969,302, incorporated herein by reference in its entirety. The CdSe nanocrystals were overcoated with zinc sulfide (ZnS). Semiconductor nanocrystals with average diameters in the range 4 to 5 nm were size selected by precipitation, reducing the distribution of sizes about the average diameter. The size-selected nanocrystals provide indicators with an emission maximum at 600 nm at ambient temperature. The absorption profile of the size-selected ZnS-capped CdSe nanocrystals was intense, having an onset of absorbance that began at approximately 600 nm and extended into the ultraviolet spectral region.

The nanocrystals are well-suited for use as luminescent temperature probes. ZnS-capped CdSe nanocrystals dispersed in a poly(lauryl methacrylate) polymer matrix provided

a material for optical measurements. A polymer rod containing nanocrystals was prepared by redispersing synthesized nanocrystals into laurylmethacrylate monomer containing TOP (5 % v/v). Then, ethyleneglycol dimethacrylate crosslinker was added to the nanocrystal-monomer solution with 1:4 volume ratio of cross-linker to monomer. After
5 azobisisobutyronitrile radical initiator (<1 % (w/w)) was added, the final solution was transferred to a 60 mm x 5 mm (length x diameter) glass tube and polymerized in an oven at 70-75°C for 2 hours. The high-clarity nanocrystal-polymer composite rod was then removed from the glass mold.

A thin disk of the polymer-supported nanocrystals was cut from the rod with a single
10 edge razor blade. The disk had a diameter of 5 mm and a thickness of approximately 1 mm. The disk was mounted flat on a surface of a temperature-controlled stage using thermal grease (CRY-CON thermal conductive grease available from Lake Shore Cryotronics). The stage was a flat surface temperature controlled with a water bath. Temperatures were maintained within ± 0.5 per degree Centigrade. The disk was irradiated with monochromatic
15 blue-green light having a wavelength of 480 nm. The emission intensity of the nanocrystals in the disk was measured at various temperatures. The temperature dependent emission spectrum of the polymer-supported nanocrystals was measured using a steady-state emission spectrophotometer. The flat disk of nanocrystals mounted on a thermostatically controlled black flat plate was orientated at a 45° angle to an incident monochromatic excitation beam.
20 Monochromatic excitation was achieved using a 200 W Hg-Xe arc lamp equipped with a Spex Model 1680B monochromator and a chopper. The emitted light intensity was measured normal to the incident excitation beam using a dry-ice cooled photomultiplier tube (Hamamatsu Type R943-02) after dispersal with a Spex Model 1870B monochromator. The background spectrum was subtracted using a Stanford Scientific Instruments photon counter.
25 Specifically, the temperature of the stage was varied from 25 to 40, 40 to 25, 25 to 15, 15 to 5, and 5 to 25 degrees centigrade. Figure 1 depicts the emission intensity of the disk at each temperature.

The decrease in emission intensity with temperature is linear. As depicted in Figure 2, the change in emission intensity was 1.3% per degree centigrade. The temperature
30 dependence of the emission intensity is not dependent on the characteristics of the sample to any great degree. The slope of the temperature dependent emission intensity does not vary

greatly from sample to sample. Generally, the slope varies from 1.1 to 1.6% per degree centigrade. The emission intensity also can be independent of excitation wavelength in the visible spectrum and is not dependent on the initial quantum yield of the sample or the supporting matrix. Furthermore, the change in emission intensity with temperature is fully reversible as indicated by the superposition of spectra obtained at 25 degrees centigrade at the beginning, middle, and end of the experiment after heating and cooling the disk. There is no hysteresis, which could indicate decomposition of the nanocrystals. Similar effects have been noted for nanocrystals dispersed in other matrices. For example, the nanocrystals can be dispersed in a sol-gel matrix. 40-50 mg of CdSe nanocrystal, either overcoated with ZnS or bare, which were washed repeatedly to remove any excess TOPO cap, are pumped dry under a vacuum and transferred into an inert atmosphere glove box. The nanocrystals were then redissolved in a solvent mixture consisting of 150 mg of tetrahydrofuran, 600 mg ethyl alcohol and 60 mg of tris-hydroxylpropyl phosphine. After stirring this solution for 10 minutes at approximately 50°C, 60-70 mg of tetrabutoxy (IV) titanate was added dropwise to this solution. The solution was then further stirred for 3 hours under the inert nitrogen atmosphere of the glove box. The films were finally prepared by spin-coating a freshly filtered nanocrystal precursor solution onto freshly cleaned microscope slides for 1 minute and then annealing for 2 minutes at 160-200°C. The spinning speed was between 3000 and 7500 rpm and decided by the desired thickness of the film. Thicker films were generated at slower spin speeds. It is necessary to eliminate exposure of the precursor solution to water prior to spin-coating, hence all the solvents used were anhydrous and the solution was allowed to pre-polymerize in the glove box.

In another example, a dispersion of nanocrystals in a binder of Dow C734, a silicone polymer was prepared. The CdSe nanocrystals were dissolved in dichloromethane at a concentration of at least 1 mM to form a nanocrystal solution. A 5:1 or 10:1 ratio of the nanocrystal solution to binder was combined and thoroughly mixed until uniform. The binder-nanocrystal solution was deposited on a glass slide or a quartz slide to form a film. Various concentrations of nanocrystal in binder were prepared such that color of the films ranged from white (low concentration of nanocrystals, ~0.1 mM) to pale in color as determined by naked eye in room light. The films were excited using with monochromatic blue-green light having a wavelength of 480 nm. The lower concentration films produced



emission that were very difficult to detect by eye, but could be easily seen with a photomultiplier tube detector. Emission from the more concentrated films was visible by eye. The emission from the higher concentration films could also be observed by eye using a hand held Hg lamp for excitation. The maximum wavelength of emission and band width of the emission are similar for nanocrystals in binder and nanocrystals in solution.

5

Other embodiments are within the scope of the following claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210